Separation tank ST-4-800

(<u>http://rozrobkinauchni.vsocorp.org/</u>). E-mail: kbgarmasch@ukr.net mob. tel. +38 095 466 23 89; +38 096 074 06 49



SEPARATION TANK ST-4-800

Separation tank. It was developed to order of the enterprise in Ukraine. The purpose of the order is to replace physically worn-out separation tanks at debit measuring stations for oil wells manufactured in the Russian Federation.

In the past, such separation tanks were developed by the «O3HA» plant in the Russian Federation.

You can order the development and production of such a separation tank by contacting us by phone or e-mail:

kbgarmasch@ukr.net

mob. tel.: +38 095 466 23 89; +38 096 074 06 49



SEPARATION TANK ST-4-800

Working environment		Oil, water, associated
Operating medium		gases +5+70
temperature, °C		13
Characteristics of the working environment	Danger class	Ш ГОСТ 12.1.007
	Explosive	Yes
	Fire hazard	Yes
Pressure, MPa	Working pressure	4,0
	Test pressure	5,4
Capacity, liter		800
Estimated vessel wall temperature, °C		100
Vessel wall temperature, °C		-60+100
Productivity on a liquid part, m ³ /day, no more		400
Productivity on a gas part, m ³ /day, no more		40000

